



E I DUPONT DE NEMOURS & CO INC

Mobility & Materials  
200 Powder Mill Road #304  
Wilmington, DE 19803 United States



Delrin: 127UV(f2)

Acetal Polyoxymethylene (POM), pellets

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL.

NOTE - (1) Material designations that are color pigmented may be followed by suffix letters and numbers. (2) Material designations may be prefixed by "ZYT" for Zytel or "MIN" for Minlon or "DEL" for Delrin or "CRA" for Crastin or "RYN" for Rynite or "ETPV" for ETPV or "SOR" for Sorona grades.

可燃性	值	测试方法
<b>UL 阻燃等级</b>		
0.8 mm, NC, BK	HB	UL 94
1.5 mm, NC, BK	HB	UL 94
3.0 mm, NC, BK	HB	UL 94
3.0 mm, NC, BK	HB40	IEC 60695-11-10, -20
0.8 mm, NC, BK	HB75	IEC 60695-11-10, -20
1.5 mm, NC, BK	HB75	IEC 60695-11-10, -20
<b>热性能</b>		
<b>RTI Elec</b>		
0.8 mm	50.0 °C	UL 746B
1.5 mm	110 °C	
3.0 mm	110 °C	
<b>RTI Imp</b>		
0.8 mm	50.0 °C	UL 746B
1.5 mm	85.0 °C	
3.0 mm	90.0 °C	
<b>RTI</b>		
0.8 mm	50.0 °C	UL 746B
1.5 mm	90.0 °C	
3.0 mm	95.0 °C	
<b>物理性能</b>		
室外适用性	f2	UL 746C