



组件 - 塑料  
UL 档案号: E45034

POLYPLASTICS CO LTD  
18-1 KONAN  
2-CHOME  
MINATO-KU, TOKYO 108-8280 Japan



Duracon: HP25X  
Acetal Polyoxymethylene (POM), pellets

| 可燃性                | 值       | 测试方法                 |
|--------------------|---------|----------------------|
| <b>UL 阻燃等级</b>     |         |                      |
| 0.8 mm, NC, WT, BK | HB      | UL 94                |
| 3.0 mm, NC, WT, BK | HB      | UL 94                |
| 3.0 mm, NC, WT, BK | HB40    | IEC 60695-11-10, -20 |
| 0.8 mm, NC, WT, BK | HB75    | IEC 60695-11-10, -20 |
| <b>热性能</b>         |         |                      |
| <b>RTI Elec</b>    |         |                      |
| 0.8 mm             | 50.0 °C | UL 746B              |
| 3.0 mm             | 50.0 °C |                      |
| <b>RTI Imp</b>     |         |                      |
| 0.8 mm             | 50.0 °C | UL 746B              |
| 3.0 mm             | 50.0 °C |                      |
| <b>RTI</b>         |         |                      |
| 0.8 mm             | 50.0 °C | UL 746B              |
| 3.0 mm             | 50.0 °C |                      |