



POLYPLASTICS CO LTD
18-1 KONAN
2-CHOME
MINATO-KU, TOKYO 108-8280 Japan



LAPEROS: S475(n2)

Liquid Crystal Polymer (LCP), pellets, aromatic

(n2) - Virgin and regrind up to 80% by weight inclusive have the same basic material characteristics with a minimum thickness of 0.10 mm.

可燃性	值	测试方法
UL 阻燃等级		UL 94 IEC 60695-11-10, -20
0.100 mm, NC, BK	V-0	
0.200 mm, NC, BK	V-0	
0.38 mm, NC, BK	V-0	
0.75 mm, NC, BK	V-0	
3.0 mm, NC, BK	V-0	
热性能	值	测试方法
RTI Elec		UL 746B
0.100 mm	130 °C	
0.200 mm	130 °C	
0.38 mm	130 °C	
0.75 mm	130 °C	
3.0 mm	130 °C	
RTI Imp		UL 746B
0.100 mm	130 °C	
0.200 mm	130 °C	
0.38 mm	130 °C	
0.75 mm	130 °C	
3.0 mm	130 °C	
RTI		UL 746B
0.100 mm	130 °C	
0.200 mm	130 °C	
0.38 mm	130 °C	
0.75 mm	130 °C	
3.0 mm	130 °C	