



组件 - 塑料  
UL 档案号: E36632

BASF CORP  
1609 BIDDLE AVE  
WYANDOTTE, MI 48192-3729 United States



Ultramid: A3Z HP

Polyamide 66 (PA66), pellets, impact modified

可燃性	值	测试方法
<b>UL 阻燃等级</b>		
0.75 mm, ALL	HB	UL 94
1.5 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
0.75 mm, ALL	HB75	IEC 60695-11-10, -20
1.5 mm, ALL	HB75	IEC 60695-11-10, -20
<b>电气性能</b>		
<b>热丝引燃 (HWI)</b>		
0.75 mm	PLC 4	UL 746A
1.5 mm	PLC 3	
3.0 mm	PLC 2	
<b>高电弧燃烧指数(HAI)</b>		
0.75 mm	PLC 0	UL 746A
1.5 mm	PLC 0	
3.0 mm	PLC 0	
<b>热性能</b>		
<b>RTI Elec</b>		
0.75 mm	65.0 °C	UL 746B
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
<b>RTI Imp</b>		
0.75 mm	65.0 °C	UL 746B
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	
<b>RTI</b>		
0.75 mm	65.0 °C	UL 746B
1.5 mm	65.0 °C	
3.0 mm	65.0 °C	